

CliniMix® 2000 Lead Safe™ TMV Replacement Cartridge (pre-2009 models only)

Product Code: 201.79.00.09



Our Australian Made lead free Galvin CliniMix® range of thermostatic mixing valves (TMVs) is designed to protect the most vulnerable from scalding or cold water shock by providing tempered water to the desired outlets that comply with the relevant Australian Standards.

The CliniMix® 2000 Lead Safe™ TMV Replacement Cartridge (pre-2009 models only) is suitable for existing 2000 TMV valves in the market marked with WMKA1593 (pre-2009). The replacement cartridge is covered under AS 4032.1 WMKA1593, ensuring its compliance. As an integral component of the thermostatic mixing valve the replacement cartridge is not separately listed on the WaterMark product database but rather included under the valve's respective item code.



Suitable for health and general applications.

Technical Information

- Outlet Temperature Adjustment Range (°C): 38 - 50
- Inlet Temperatures:
 - Cold Supply (°C): 5 Min - 25 Max
 - Hot Supply (°C): 55 Min - 90 Max
 - Hot to Mix Temp Differential (°C): 10 Min
 - Cold to Mix Temp Differential (°C): 5 Min

- Flow Rates to Ensure Stable Conditions:
 - Minimum (LPM): 4 Min
 - Maximum (LPM): 38 Max @ 300kPA pressure loss
- Dynamic Inlet Pressures - Hot and Cold (kPa): 20 Min - 550 Max
- Static Inlet Pressures - Hot and Cold (kPa): 1600 Max

This product is compatible with

- 201.70.02.00 CliniMix® 2000 Lead Safe™ 3/4" Thermostatic Mixing Valve



Environmental Sustainability

We are ISO 14001 certified and take sustainability seriously. Our products are environmentally responsible designed to be healthier for users, save water and/or energy, and minimise carbon footprint. Our target is to reduce our carbon footprint by 25%, and the use of non-recyclable/non-compostable materials across the company (e.g. plastics) by 50%.

Warranty

Galvin Engineering products are covered under our Manufacturer’s Warranty. Galvin Engineering products must be installed in accordance with the installation instructions and in accordance with AS 3500 and NCC Volume Three, relevant Australian Standards and local authorities applicable to product being installed. Water and electrical supply conditions must also comply to the applicable national and/or state standards, failing to comply with these provisions may void the product warranty and affect performance of the product.

Please visit www.galvinengineering.com.au to view the full warranty, our Installation Compliance and Maintenance & Cleaning information as well as any other additional information.

While all reasonable care has been taken in compiling the information in this document, the designs, dimensions and products shown are indicative only and should not be relied upon without our prior approval. Due to our policy of continuous development, we reserve the right to alter any details of specifications or products without notice. All information, drawings, technical specifications and product designs remain the property of Galvin Engineering Pty Ltd.

Our Lead Safe™ product range is compliant with the Lead Free Requirements of the NCC 2022 Vol. Three, Clause A5G4(2) and NSF/ANSI 372.

Within Australia: 1300 514 074
Outside Australia: P: +61 (0)8 9338 2344
sales@galvinengineering.com.au
www.galvinengineering.com.au



A family
owned
Australian
business

