


Flowmatic® Concealed Sensor Assembly with SS Face Plate & CliniLever® Fixed Wall Outlet 225

Product Code: TZ-FLOWTAPC225











The Galvin Flowmatic[®] wall sensor and outlet combination is designed to be mounted flush into the wall or trough and provide a low profile finish to help minimise the build-up of dirt or bacteria. Combined with its handsfree operation and self-draining laminar flow spout it minimises the risk of infection for staff and patients. The multiple time cycle options are adjustable on-site, allowing the facility manager full flexibility to adjust as required.

Features

Electronic Sensor

- Sensor face is designed to be mounted flush into wall/trough to minimise dirt or bacteria growth (sensor eye and screws supplied)
- Sensor circuit boards are supplied standard with a lacquer finish to limit moisture damage
- · Multiple time cycle options are adjustable on-site allowing full flexibility to suit user requirements
- Built-in capacitors and easy fit electrical filters to help suppress external noise, and provide continuous reliable water delivery
- Bluetooth Connectivity allows facility managers to program-specific hygiene times and other features
- Australian Made; therefore, spare parts and support are available locally, reducing maintenance and downtime costs

Spout

- · Angled spout to help minimise the storage of unused water and reduce the spread of Legionella
- · Laminar nozzle supplied standard to reduce the risk of Legionella spread
- · Bright chrome-plated finish for easy cleaning, added durability and hygiene maintenance

Solenoid

- 24-volt low power usage solenoid to reduce power usage and costs
- Quiet closing to minimise the impact of water hammer within the plumbing system

Technical Information

• WELS: 4 Star Rating (5.5L/min)

• Nominal Flow Rate (LPM): 5.0

• WaterMark: AS 3718 Lic. WMKA0034

• Inlet: 1/2" BSP - Female

· Outlet: Laminar Flow Aerator

· Headwork: Solenoid

• Working Pressure Range (kPa): 50 Min - 500 Max

• Working Temperature Range (°C): 5 Min - 90 Max

• Finish: Brushed Stainless Steel Sensor Plate and Chrome Outlet



Environmental Sustainability

We are ISO 14001 certified and take sustainability seriously. Our products are environmentally responsible designed to be healthier for users, save water and/or energy, and minimise carbon footprint. Our target is to reduce our carbon footprint by 25%, and the use of non-recyclable/non-compostable materials across the company (e.g. plastics) by 50%.

Warranty

Galvin Engineering products are covered under our Manufacturer's Warranty. Galvin Engineering products must be installed in accordance with the installation instructions and in accordance with AS 3500 and NCC Volume Three, relevant Australian Standards and local authorities applicable to product being installed. Water and electrical supply conditions must also comply to the applicable national and/or state standards, failing to comply with these provisions may void the product warranty and affect performance of the product.

Please visit www.galvinengineering.com.au to view the full warranty, our Installation Compliance and Maintenance & Cleaning information as well as any other additional information.

While all reasonable care has been taken in compiling the information in this document, the designs, dimensions and products shown are indicative only and should not be relied upon without our prior approval. Due to our policy of continuous development, we reserve the right to alter any details of specifications or products without notice. All information, drawings, technical specifications and product designs remain the property of Galvin Engineering Pty Ltd.

Within Australia: 1300 514 074
Outside Australia: P: +61 (0)8 9338 2344
sales@galvinengineering.com.au
www.galvinengineering.com.au





